

Wall mounted socket

Part no. 9530




- screw terminals
- highly resistant to chemicals
- highly heat resistant contact carrier
- nickel plated contacts
- two external fixing points
- sockets are designed for adding an auxiliary contact switch
- enclosure base can be turned 180°

Technical specifications

| | |
|-----------------------|---|
| Ampere | 16 A |
| Poles | 7 p |
| Voltage | 230 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | nickel plated contacts, highly heat resistant contact carrier |
| Protection type | IP67 |
| Enclosure material | Plastic, high resistance to chemicals / AMELAN |
| Weight | 213 g |
| Certifications | EAC |

Drawing



| Drawing | Amp. | 16 | 32 |
|--|----------------------------|----------------------------|-------------------|
| 1 MB 622 | Poles | 7 | 7 |
| Dim. in mm | a | 100 | 100 |
| | b | 101 | 109 |
| | c | 131 | 160 |
| | d | 50 | 50 |
| | e | 84 | 92 |
| | f1 | 5.3 | 5.3 |
| | f2 | 5.3 | 5.3 |
| | g | 6.5 | 6.5 |
| | h | 132 | 148 |
| | i | 24.7 | 27.5 |
| | M | 25 (optional M20) | 32 (optional M25) |
| M* | 2x25 (blind) to be cut out | 2x25 (blind) to be cut out | |
| Max. cable diam. (mm) | 18 (M25) and 15 (M20) | 25 (M32) and 18 (M25) | |
| Terminal for cond. cross section (mm²) min.-max. | 1.5 | 2.5 | |
| | —4 | —6 | |